

ISUZULT BUS

-Bus Chassis-

Item/Model		LT134PL5		
Weight	GVW	kg	14,500	
	Chassis weight	kg(約)	4,730	
Dimensions	Length	mm	11,175	
	Width	mm	2,464	
	Height	mm	1,800	
	Wheelbase	mm	5,700	
	Track	Front	mm	1,966
		Rear	mm	1793
Ground Clearance		mm	300	
Engine	Type	6HK1E5N Four cycle, water cooled, OHC, Diesel, direct injection with turbo charger intercooler		
	Displacement	c.c.	7,790	
	Power	PS/rpm (Net)	240/2,400	
	Torque	N-m/rpm (Net)	706(Approx.72kg-m)/1,450	
	Compression Ratio		17.5	
	Fuel Tank	L	200	
Transmission	Type	Forward 6, Reverse 1		
	Gear Ratio	6.615/4.095/2.358/1.531/1.000/0.722/Reverse6.615		
	Final Gear Ratio	5.857		
Clutch	Dry single plate			
Performance	Max. Speed	km/h	109	
	Gradeability	tan θ%	35	
	Min. Turning Radium		9.88	
Suspension	Front / Rear	parabolic leaf spring with hydraulic shock absorber		
Electric System	Battery	V/AH	12/150 x 2	
	Generator	V/A	24/120	
Brake	Brake system	Hydraulic vacuum assisted dual circuit, Exhaust brake, ABS		
	Type	Front Drum, Rear Drum		
Tire	Front Wheel / Rear Wheel	295/80R22.5		

1. The model meets the EURO 5 environment regulation.
2. Catalogue is only for reference, the actual specification follows by the physical car.
3. Company has the right to modify or terminate the specification of products without any advanced notification.
4. The GVW can be varied by different bodies and specifications that follows the safety standard of Ministry of Transportation.