## All New Euro 5 **NPR 7.5 T** Spec Sheet

Fea	atures/N	lodel		NPR75FM5(AT)/NPR75FA5(AMT)	NPR75HM5(AT)/NPR75HA5(AMT)	NPR75KM5( AT )/NPR75KA5( AMT )				
	GVW kg		kg	7,500						
Weight	Chassis Weight kg		kg	2,680 ( <b>AT</b> ) / 2,715 ( <b>AMT</b> )	2,715 ( <b>AT</b> ) / 2,750 ( <b>AMT</b> )	2,745 ( <b>AT</b> ) / 2,780 ( <b>AMT</b> )				
	Model			Short Axis , Luxury High Cab	Mid Axis , Luxury High Cab	Long Axis , Luxury High Cab				
	Number of passengers			3						
Size	Overall Length mm		mm	5,135	5,985	6,635				
	Overall Width mm		mm	2,115						
	Overall Height mm			2,275						
	WheelBase mm		mm	2,765	3,365	3,815				
	(Front)		mm							
	Track	(Rear)	mm	1,650						
	Ground Clearance mm		mm	161						
	Type 4HK1E5N			Direct injection 4 cycle water cooler 4 cylinder(OHC) common rail diesel engine with turbo(VGS) , EGR , Catalyst and DPD						
	Displacement C.C.			5,193						
	Max. Output PS / rpm (Net)			155/2,600						
Engine	Max. Torque N-m / rpm (Net)			419(≒ 42.8kg-m) /1,600~2,600						
	Compression ratio			17.5						
	Fuel Tank Capacity			100						
	Туре			6 forward , 1 reverse						
Transmission	Gear Ratio			5.979 / 3.434 / 1.862 / 1.297 / 1.000 / 0.759 / 5.701						
	Final Gear Ratio			4.3						
Clutch				Dry Single-Plate Hydraulically Operated(MT) / Wet Multi-Plate Hydraulically Operated(AT)						
	Max. Speed km		km / h	115						
Performance	Gradeabil	ity t	anθ%		39					
	Min. Turni	ing Radiu	s m	5.1	6.3	7.1				
Suspension	Front / Re	ar		Half elliptic leaf spring with Hydralic buffer						
Electric	Battery V / AH		V / AH	12 / 69 x 2						
	Generator V / A		V/A	24 / 90						
Brake	Service Brake			Hydraulic , Dual Circuit , with Exhaust Brake and ABS						
	Туре			Front Drum / Rear Drum						
Tire	Front / Rear			215 / 75R17.5						
Others	Drive Cab			Convertible						
	Air Conditioner			Cold and Heat						

1. This catalog is for reference only, specifications in kind prevail. 2. TTM reserve the right to change specifications without prior notice.

	OAL	WB	FOH	ROH	CA	CE	AW	EH	НН
NPR75FM5	5,135	2,765	1,110	1,260	2,192	3,452	1,680	800	161
NPR75FA5	5,155								
NPR75HM5	5,985	3,365	1,110	1,510	2,792	4,302	1,680	800	161
NPR75HA5	3,905								
NPR75KM5	6,635	3,815	1,110	1,710	3,242	4,952	1,680	800	161
NPR75KA5	0,035								





