All New Euro 5 NQ R9.5 T Spec Sheet [155 / 190 PS]

Fe	atures/	Mode		NQR90HM5	NQR90KM5	NQR90HMH5	NQR90KMH5	NQR90LMH5			
Weight	GVW kg				9,500						
	Chassis Weight kg		2,890	2,990	2,915	2,925	2,950				
	Model		Short Axis , Luxury High Cab	Long Axis , Luxury High Cab	Short Axis , Luxury High Cab	Long Axis , Luxury High Cab	Extra Long Axis , Luxury High Cab				
	Number of passengers					3					
Size	Overall Length mm		5,985	6,635	5,985	6,635	7,355				
	Overall Width mm		2,130								
	Overall Height mm										
	WheelBase		mm	3,365	3,815 3,365		3,815	4,175			
	Track	(Front)	mm	1,680							
	- Truck	(Rear)	mm	1,650							
	Ground Clearance mm					185					
Engine	Туре			4HK1E5N 4HK1E5C							
				Direct injection 4 cycle water cooler 4 cylinder(DOHC) common rail diesel engine with turbo(VGS), EGR, Catalyst and DPD							
	Displacement C.C.			5,193							
	Max. Output PS / rpm (Net)			155/2		190/2,600					
	Max. Torque N-m / rpm (Net)			419(≒ 42.8kg-m) /1,600~2,600 513(≒ 52.3kg-m) /1,600~2,600							
	Compression ratio			17.5							
	Fuel Tank Capacity			100							
Transmission	Туре			6 forward , 1 reverse							
	Gear Ratio			5.979 / 3.434 / 1.862 / 1.2	297 / 1.000 / 0.759 / 5.701	6.369 / 3.767 / 1.966 / 1.355 / 1.000 / 0.782 / 6.369					
	Final Gear Ratio			4.3							
Clutch				Dry Single-Plate Hydraulically Operated							
Performance	Max. Speed km / h			14	121						
	,		tan θ%		7	0.0	34	7.0			
	Min. Turn		ius m	6.3	7.1	6.3	7.1	7.6			
Suspension	Front / Rear			Half elliptic leaf spring with Hydralic buffer							
Electric	Battery V/AH			12 / 55 x 2 24 / 80							
Brake	Generator V / A			Full Air , Dual Circuit , with Exhaust Brake and ABS							
	Service Brake Type			Full Air , Dual Circuit , with Exhaust Brake and ABS Front Drum / Rear Drum							
Tire	Front / Rear			225 / 75R17.5							
Others	Drive Cab			Convertible							
	Air Conditioner			Cold and Heat							
	7.11 CONGREGATE					Cold and Heat					

 $1. This\ catalog\ is\ for\ reference\ only\ , specifications\ in\ kind\ prevail\ .\ \ 2. TTM\ reserve\ the\ right\ to\ change\ specifications\ without\ prior\ notice\ .$

	OAL	WB	FOH	ROH	CA	CE	AW	EH	нн
NQR95HM5	5,985	3,365	1,110	1,510	2,790	4,300	1,680	775	185
NQR95KM5	6,635	3,815	1,110	1,710	3,240	4,950	1,680	775	185
NQR95HMH5	5,985	3,365	1,110	1,510	2,790	4,300	1,680	775	185
NQR95KMH5	6,635	3,815	1,110	1,710	3,240	4.950	1,680	775	185
NQR95LMH5	7,355	4,175	1,110	2,070	3,600	5,670	1,680	775	185





