

FVR 17T Spec Sheet

Features/Model		FVR34LP5	FVR34LS5	FVR34LT5	
Weight	GVW	kg	17,000		
	Chassis Weight	kg	5,460	5,615	5,685
	Number of passengers		3人		
Size	Overall Length	mm	8,505	10,005	10,740
	Overall Width	mm	2,475		
	Overall Height	mm	2,805		
	WheelBase	mm	5,050	6,050	6,500
	Track	(Front)	mm	1,990	
		(Rear)	mm	1,850	
	Ground Clearance	mm	230		
Engine	Type	6HK1E5C	Direct injection 4 cycle water cooler 6 cylinder(OHC) common rail diesel engine with turbo(VGS)and Intercooler , EGR , Catalyst and DPD		
	Displacement	c.c.	7,790		
	Max. Output	PS/rpm (Net)	260/2,400		
	Max. Torque	N-m/rpm (Net)	761 (≒77.6kg-m) /1,450-2,400		
	Compression ratio		16.5		
	Fuel Tank Capacity	L	200		
Transmission	Type	ZF9S1110	Manual , 9 forward 1 reverse synchromesh transmission with power support		
	Gear Ratio		L 9.479 / 6.576 / 4.678 / 3.478 / 2.617 / 1.890 / 1.345 / 1.000 / 0.752 / R 8.967		
	Final Gear Ratio		5.571		
Clutch		Dry Single-Plate , Air Pressure support			
Performance	Max. Speed	km/h	110		
	Gradeability	tan θ %	60		
	Min. Turning Radius	m	8.3	9.8	10.5
Suspension	Front / Rear	Half elliptic leaf spring with Hydraulic buffer / Half elliptic leaf spring			
Electric	Battery	V/AH	12/110*2		
	Generator	V/A	24/60 (90A OPT)		
Brake	Service Brake		Full Air , Dual Circuit , ABS with Automatic Brake Regulator		
	Type		Front Drum / Rear Drum		
	Auxiliary Brake		Exhaust Brake		
Tire	Front / Rear	295/80R22.5			
Others	Drive Cab		Convertible		
	Air Conditioner		Cold and Heat		
	Steering		Power Steering		

1.This catalog is for reference only , specifications in kind prevail . 2.TTM reserve the right to change specifications without prior notice .

	OAL	WB	FOH	ROH	CA	CE	AW	EH	HH
FVR34LP5	8,505	5,050	1,440	2,015	4,424	6,439	1,990	1,088	230
FVR34LS5	10,005	6,050	1,440	2,515	5,424	7,939	1,990	1,088	230
FVR34LT5	10,740	6,500	1,440	2,800	5,874	8,674	1,990	1,088	230

