All New Euro 5 NPR 7.5 T Spec Sheet

Fea	ntures/N	Nodel		NPR75FM5(MT)/NPR75FA5(AMT)	NPR75HM5(MT)/NPR75HA5(AMT)	NPR75KM5(MT)/NPR75KA5(AMT)					
	GVW kg		kg	7,500							
Weight			kg	2,680 (MT) / 2,715 (AMT)	2,715 (MT) / 2,750 (AMT)	2,745 (MT) / 2,780 (AMT)					
	Model			Short Axis , Luxury High Cab	Mid Axis , Luxury High Cab	Long Axis , Luxury High Cab					
	Number of passengers				3						
Size	Overall Length mm		mm	5,135	5,985	6,635					
	Overall Width mm			2,115							
	Overall Height mm			2,275							
	WheelBase mr		mm	2,765	3,365	3,815					
	Track	(Front)	mm		1,680						
	ITACK	(Rear)	mm		1,650						
	Ground Clearance mm		mm	161							
Engine	Type 4HK1E5N		K1E5N	Direct injection 4 cycle water cooler 4 cylinder(OHC) common rail diesel engine with turbo(VGS), EGR, Catalyst and DPD							
	Displacement C.C.		C.C.	5,193							
	Max. Output PS / rpm (Net)			155/2,600							
	Max. Torque N-m / rpm (Net)			419(≒ 42.8kg-m) /1,600~2,600							
	Compression ratio			17.5							
	Fuel Tank Capacity			100							
	Туре			6 forward , 1 reverse							
Transmission	Gear Ratio			5.979 / 3.434 / 1.862 / 1.297 / 1.000 / 0.759 / 5.701							
	Final Gear Ratio			4.3							
Clutch				Dry Single-Plate Hydraulically Operated(MT) / Wet Multi-Plate Hydraulically Operated(AT)							
Performance	Max. Speed km / h		km/h	115							
	Gradeabi	lity ta	an θ%		39						
	Min. Turn	ing Radiu	s m	5.1	6.3	7.1					
Suspension	Front / Re	ear		Half elliptic leaf spring with Hydralic buffer							
Electric	Battery V / AH		V / AH	12 / 69 x 2							
	Generator V / A		V/A	24 / 90							
Brake	Service Brake			Hydraulic , Dual Circuit , with Exhaust Brake and ABS							
	Туре			Front Drum / Rear Drum							
Tire	Front / Rear			215 / 75R17.5							
Others	Drive Cab			Convertible							
	Air Conditioner			Cold and Heat							

 $1. This\ catalog\ is\ for\ reference\ only\ , specifications\ in\ kind\ prevail\ .\ \ 2. TTM\ reserve\ the\ right\ to\ change\ specifications\ without\ prior\ notice\ .$

	OAL	WB	FOH	ROH	CA	CE	AW	EH	НН
NPR75FM5	5,135	2,765	1,110	1,260	2,192	3,452	1,680	800	161
NPR75FA5	37.33								
NPR75HM5	5.985	3,365	1,110	1,510	2,792	4,302	1,680	800	161
NPR75HA5	3,703								
NPR75KM5	6,635	3,815	1,110	1,710	3,242	4,952	1,680	800	161
NPR75KA5	0,033								





